



INFORMACIÓN PARA EL USUARIO



Este producto se ha fabricado siguiendo las exigencias del Reglamento UE 2016/425, para su uso básico, según la norma EN ISO 13688:2013 (Ropa de protección. Requisitos generales) y UNE-EN ISO 20471:2013+A1:2016 (ropa de alta visibilidad) que le son aplicables.

Organismo Notificado 2895, Shirley® Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI.

Este EPI está confeccionado en poliéster color amarillo fluorescente, con bandas reflectantes y se ha concebido para proteger a su usuario en aquellas situaciones de alto riesgo de baja visibilidad.

La consecución de las prestaciones de la prenda requiere que la misma se encuentre correctamente cerrada y en buen estado de mantenimiento.

Esta prenda puede ser utilizada con otros equipos de protección individual siempre y cuando no se oculte ni el tejido fluorescente ni el material reflectante.

Recomendaciones contra el mal uso:

Nunca debe usarse el presente EPI frente a otros riesgos que los anteriormente descritos.

El mal mantenimiento de las prendas puede modificar las prestaciones de las mismas.

Cuando la prenda esté constituida por dos piezas, el usuario debe llevarlas conjuntamente para conseguir el nivel de protección adecuado.

Los rasgados no deben ser reparados por el usuario.

No modificar o alterar la prenda

Para asegurar su efectividad, la prenda debe mantenerse limpia y ser sustituida en caso de encontrarse descolorida o con manchas permanentes que no puedan eliminarse.

Es recomendable realizar comparaciones regulares con una unidad nueva para asegurarse del estado de la prenda

CUIDADO DE LA PRENDA

Max. 25 ciclos lavado

No sumergir en desengrasante ni utilizar lejía o jabones agresivos.

Planchar a baja temperatura y nunca sobre las bandas reflectantes.

No se permite limpieza en seco ni secado en secadora.

Almacenar en lugares secos, protegidos de cualquier agente agresivo y evitando su innecesaria exposición solar.

Una vez alcanzado el final de la vida útil, esta prenda debe ser desechada adecuadamente. Los materiales textiles pueden reciclarse.



INFORMACIÓN ADICIONAL

CLASES DE PROTECCIÓN	CLASE 3	CLASE 2	CLASE 1
Material de Fondo	0,80 m ²	0,50 m ²	0,14 m ²
Material Retrorreflectante	0,20 m ²	0,13 m ²	0,10 m ²
Material de efecto combinado	-	-	0,20 m ²

El número máximo de lavados especificado no es el único factor del que depende la vida útil de la prenda.

La vida útil también dependerá del uso del EPI, mantenimiento, almacenamiento...

TALLA	PECHO (cm)	ALTURA (cm)
S	100-106	158-164
M	106-112	164-170
L	112-118	170-176
XL	118-124	176-182
XXL	124-130	182-188
XXXL	130-136	188-194

CAZADORA ALTA VISIBILIDAD

Mod. Bomber-Xenon

05-0005



Con mangas



Sin mangas

UNE-EN ISO 20471:2013+A1:2016

EN ISO 13688:2013

Cat. II

BLASCAT[®]

USER's MANUAL

This product has been manufactured in accordance with the requirements of EU Regulation 2016/425, for its basic use, according to EN ISO 13688:2013 (Protective clothing. General requirements) and UNE-EN ISO 20471:2013+A1:2016 (High-visibility clothing) that are applicable to it. Notified Body (NB) number 2895, Shirley Technologies (Europe) Limited. Sky Business Centre, Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI.

This PPE is made of fluorescent yellow polyester, with reflective stripes. It has been designed to protect the wearer in high risk situations of low visibility and rain.

In order to achieve the performance of the jacket, it must be properly closed and in a good state of maintenance.

This article can be used with other PPE as long as neither the fluorescent fabric nor the reflective material is hidden.

Recommendations against misuse:

The present PPE should never be used against risks other than those described above.

Incorrect maintenance of the garments may modify their performance.

When the garment is made up of two pieces, the user should wear them together to achieve the appropriate level of protection.

Rips should not be repaired by the wearer.

Do not modify or alter the garment.

To ensure its effectiveness, the garment should be kept clean and replaced if found to be discolored or with permanent stains that cannot be removed.

It is advisable to make regular comparisons with a new unit to ensure the condition of the item.

GARMENT CARE

Max. 25 wash cycles

Do not soak in degreaser or use bleach or aggressive soaps.

Iron at low temperature and never on the reflective stripes.

Do not dry clean or tumble dry.

Store in dry places, protected from any aggressive agent and avoiding unnecessary exposure to sunlight.

Once the garment has reached the end of its useful life, it should be thrown away properly. Textile materials can be recycled.



ADDITIONAL INFORMATION

TYPES OF PROTECTION	CLASS 3	CLASS 2	CLASS 1
Background material	0,80 m ²	0,50 m ²	0,14 m ²
Reflective material	0,20 m ²	0,13 m ²	0,10 m ²
Combined material	-	-	0,20 m ²

AJJ Stores S.A. CIF. A24428161, P. I. La Sementera C/ La Hemina B2 24750 La Bañeza (León-Spain)

You can access the Declaration of conformity in www.ajjgrupo.com or contacting us in ajj@ajjgrupo.com



HIGH VISIBILITY JACKET
Mod. Bomber-Xenon
05-0005



With sleeves



Without Sleeves

UNE-EN ISO 20471:2013+A1:2016

EN ISO 13688:2013
Cat. II

The maximum number of washes specified is not the only factor on which the service life of the garment depends.

The service life will also depend on the use, maintenance, storage,... of the PPE.

SIZE	CHEST (cm)	HEIGHT (cm)
S	100-106	158-164
M	106-112	164-170
L	112-118	170-176
XL	118-124	176-182
XXL	124-130	182-188
XXXL	130-136	188-194